

Filtering half mask			
<b>FS-613V FFP1 NR D</b>			
Certificate UE/345/2020/1437	Date of issue 3/24/2020	Standard EN 149:2001 + A1:2009	Protection class Class P1 
Certification body:  CIOP-PIB 1437 Central Institute for Labour Protection – National Research Institute		 	
Supervising body:  CIOP-PIB 1437* Central Institute for Labour Protection – National Research Institute			

## Intended use

For protecting the user's respiratory tract against the harmful impact of air pollution in the form of solid and/or liquid particles forming aerosol (dust, fumes, mists) up to 4 × TLV.

## Application

Non-toxic dust, agricultural industry, food industry, quarry, cement plants; especially for dusts such as calcium carbonate, natural and synthetic graphite, gypsum, chalk, cement, plaster, marble, zinc oxide, pollen, cellulose, sulphur, cotton, ferrous metal filings, coal dust containing less than 10% of free silica.

## Specification

Half mask face-piece:

- Needle-punched nonwoven polyester
- Melt-blown nonwoven polypropylene
- Protective nonwoven

Additional elements:

- Exhalation valve
- Head band pins for length adjustment
- Head band

You no longer have to waste time trying to adjust the nosepiece to fit your face and your glasses will not fog up. 600-SERIES half masks are equipped with pins for head band length adjustment, which improves facial fit and, as a result, half mask performance.

Filtering half mask			
<h2>FS-613V FFP1 NR D</h2>			
Certificate UE/345/2020/1437	Date of issue 3/24/2020	Standard EN 149:2001 + A1:2009	Protection class Class P1 
Certification body: CIOP-PIB 1437 Central Institute for Labour Protection – National Research Institute			
Supervising body: CIOP-PIB 1437* Central Institute for Labour Protection – National Research Institute			

## Requirements

The half mask meets the latest requirements:

**Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment** and repealing Council Directive 89/686/EEC.

## Contraindications

The half mask must not be used under low-oxygen conditions (below 17%), which means that it is forbidden to use it in confined spaces, such as canals, manhole shafts, tanks. Also, the half mask does not protect against vapours and gases that are harmful for health and pose a life hazard. Do not use while extinguishing fire. The half mask does not supply oxygen. The half mask will not provide adequate facial fit for people with unshaved or bearded face. The half mask does not protect against aerosols containing radioactive and carcinogenic particles, microorganisms (bacteria, viruses, fungi and their derivatives) or enzymes.

Primary packaging: 50 pcs per plastic bag

Collective packaging: 400 pcs per carton

\*This number is on the product after the CE mark