

Filter Service Sp. z o.o.
ul. Sadowa 7a
95-100 Zgierz

Tel/Fax: (+48 42) 716 15 18
Tel/Fax: (+48 42) 717 15 81
Fax: (+48 42) 717 15 15
Fax: (+48 42) 715 44 33
Email: filter@filter-service.eu
www.filter-service.eu

Filtering half mask

FS-920 A FFP2 NR D

Certificate

UE/974/2024/1437
Edition 1

Date of issue

01.03.2024

Standard

EN 149:2001 + A1:2009

Protection class

Class P2



Certification body:

CIOP-PIB 1437
Central Institute for Labour
Protection – National
Research Institute

Supervising body:

CIOP-PIB 1437*
Central Institute for Labour
Protection – National
Research Institute



Intended use

For protecting the user's respiratory tract against the harmful impact of air pollution in the form of solid and/or liquid particles forming aerosol (dust, fumes, mists) up to 10 × TLV.

Application

Medium-toxic particulate matter, dusts of asbestos, copper, barium, titanium, vanadium, chromium, manganese, wood dusts, coal dust containing more than 10% of free silica, mining industry, chemical industry, metallurgical industry (the version with the exhalation valve).

Specification

Half mask dome:

- Protective non-woven fabric
- Structural non-woven polypropylene fabric
- Non-woven polypropylene melt blown fabric
- Protective non-woven fabric

Additional elements:

- Nosepiece for better facial fit within the nose area
- Polyethylene foam nose seal
- Head band

Thanks to the production automation and optimisation, 900-series half masks are available for an attractive price.

It is an economical alternative to disposable respiratory protective equipment available on the market with no compromises on product quality.

Filtering half mask	
<h2>FS-920 A FFP2 NR D</h2>	
Certificate UE/974/2024/1437 Edition 1	Date of issue 01.03.2024
Standard EN 149:2001 + A1:2009	Protection class Class P2 
<div> <div> Certification body: CIOP-PIB 1437 Central Institute for Labour Protection – National Research Institute </div> <div> Supervising body: CIOP-PIB 1437* Central Institute for Labour Protection – National Research Institute </div> </div>	
<div>   </div>	

Requirements

The half mask meets the latest requirements:

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC.

Contraindications

The half mask must not be used under low-oxygen conditions (below 17%), which means that it is forbidden to use it in confined spaces, such as canals, manhole shafts, tanks. Also, the half mask does not protect against vapours and gases that are harmful for health and pose a life hazard. Do not use while extinguishing fire. The half mask does not supply oxygen. The half mask will not provide adequate facial fit for people with unshaved or bearded face. The half mask does not protect against aerosols containing radioactive and carcinogenic particles, microorganisms (bacteria, viruses, fungi and their derivatives) or enzymes.

Primary packaging: 10 pcs per plastic bag

Collective packaging: 500 pcs per carton

*This number is on the product after the CE mark